



Logan Smith  
April 15, 2026 1:33 PM



12932

NOTICE OF  
NUISANCE &  
ORDER TO  
ABATE

NOTICE OF  
VIOLATION

Logan Smith  
April 15, 2026 1:33 PM



Logan Smith  
April 15, 2026 1:34 PM



Logan Smith

April 29, 2026 1:43 PM



Logan Smith  
April 29, 2026 1:43 PM



Logan Smith

September 11, 2025 12:58 PM



Logan Smith

October 08, 2025 1:39 PM



Logan Smith

October 08, 2025 1:36 PM



Thickness (in)	R-Value (per inch)
0.50	2.7
1.00	5.0
1.50	7.5
2.00	10.0

Seal and  
with EYE STAR

**CODE COMPLIANCE**  
AP Foil Faced Polyiso Continuous Insulation complies with the following code requirements:  
1. ICC-ES ESR-3268, CCMC 13104-L  
2. ASTM E2539, Type I, Class 1  
3. CAN/ULC-S704, Type 1, Class 1

**WARNING:** Johns Manville AP Foil Faced Polyiso Continuous Insulation is combustible and shall only be used as specified by the local building code with respect to flame spread classification and to the use of a suitable thermal barrier when required.  
**PRECAUCION:** El recubrimiento Johns Manville AP es combustible y debe ser usado de acuerdo con lo especificado en el código de construcción local con respecto a la clasificación de la propagación de flama y al uso de barreras térmicas cuando se requiera.

Logan Smith  
October 08, 2025 1:36 PM



Logan Smith  
October 08, 2025 1:35 PM



Logan Smith  
October 08, 2025 1:35 PM

2.00	16	76	3.94	4.31
2.50	19	89	4.52	4.88
3.00	22	102	5.09	5.45
3.50	25	114		
4.00	28			
4.50				

Aged R-value at 75° F in accordance with ASTM C1289.  
Design UTR determined by CAN/ULC-S770 in accordance with CAN/ULC-S708.  
R stands for resistance to heat flow. The higher R-value, the greater the insulating power.  
© 2017 Johns Manville. All Rights Reserved.

**JM Johns Manville**  
A Berkshire Hathaway Company

**JM Johns Manville**  
A Berkshire Hathaway Company

AP Foil-Faced  
Polyiso Core

AP Foil-Faced  
polyiso continuous insulation



Johns Manville Polyiso Continuous Insulation (CI) is as specified by the local building code with respect to the use of a suitable thermal barrier.

**CODE COMPLIANCE**  
 ICC-ESR-3389, CCIMC 13104.1  
 AP Foil-Faced Polyiso Continuous Insulation complies with the following standards and model codes when properly installed:

**Seal and Insulate with ENERGY STAR**  
 LEARN MORE AT [energystar.gov](http://energystar.gov)

**WARNING:** Johns Manville AP Foil-Faced Polyiso Continuous Insulation is combustible and shall only be used in accordance with the applicable code classification and listing. See the manufacturer's literature for details.  
**PRECAUCION:** El aislamiento de Johns Manville AP Foil-Faced Polyiso Continuous Insulation es combustible y debe ser utilizado de acuerdo con la clasificación y listado aplicables. Véase la literatura del fabricante para obtener más detalles.

RSI-Value ("K·m <sup>2</sup> /W)	Design LTR ("K·m <sup>2</sup> /W)
0.48	0.48
0.62	
0.88	
1.06	
1.32	
1.63	

Thickness (in)	R-Value (ft <sup>2</sup> ·°F·h/BTU)	Thickness (mm)	RSI-Value ("K·m <sup>2</sup> /W)	Design LTR ("K·m <sup>2</sup> /W)
0.50	2.7	13	0.48	0.48
0.62	3.5	16	0.62	0.61
0.75	5.0	19	0.88	0.83
1.00	6.0	25	1.06	1.02
1.20	7.5	31	1.32	1.26
1.50	9.3	38	1.63	1.57
1.65	10	42	1.82	1.74

1	2
3	4
5	6
7	8



Logan Smith  
 October 08, 2025 1:35 PM



Logan Smith  
October 08, 2025 1:34 PM



Logan Smith  
October 08, 2025 1:40 PM



Logan Smith

October 08, 2025 1:40 PM



Logan Smith

October 08, 2025 1:43 PM