NORCAL KENWORTH-BAY AREA

1755 ADAMS AVE. - SAN LEANDRO, CA 94577 TELEPHONE: (510)836-6100 FAX: (510)836-2270

PURCHASE ORDER DE-07105/2018-03747

NORCAL KENWORTH-SACRAMENTO

707 DISPLAY WAY - SACRAMENTO CA 95838 TELEPHONE: (916)371-3372 FAX: (916)371-0737

NORCAL KENWORTH-ANDERSON

20769 INDUSTRY RD. - ANDERSON, CA 96007 PH:(530)222-1212 FAX:(530)722-0934

NORCAL KENWORTH-MORGAN HILL
16715 CONDIT RD MORGAN HILL, CA 95037
PH: (408)842-5383 FAX: (408)843-9699

BIT IND. MORGANTINEE, OF COOCT
3)842-5383 FAX: (408)843-9699
LAKE COLINITY SHERRIE'S OFFICE

NAME LAKE COUNTY S	HERRIF'S OF	FICE		27	DATE	04/24/2018	
ADDRESS 4913 Helbush Driv	e Lakeport, C	a 95453			TELEPHONE	(707)262-40	89
PLEASE ENTER MY			OWS:	-			
QUANTITY X NEW YEAR USED 2019		MODEL T370	# OF AXLES	COL		USED TRK#	SALESPERSON Jim Matthews
MILEAGE WEIGHT 33000		EXPIRATION		ELIVERY DATE		SERIA	AL NUMBER
BODY DESCRIPTION:Tractor			COUNTY: Lake				
REMARKS					PRICE (PER		\$72,859.00
2019 Kenworth T370 2 a	xle tractor			Dealers Fee	s - Not inclu	ded in NJPA	\$1,100.00
per specifications dated							
Kenworth NJPA #081716	S-KTC			-			
Renworth Not A #0017 To)-I(10						
LEGAL OWNER:							
					SUBTOTAL		\$73,959.00
	UNIESSTH	IE MANUFACTL	IRER OR THE	FED	ERAL EXCISE	TAX	\$0.00
PHYSICAL DAMAGE YES XN	O DEALER HAS	ISSUED SPECI	FIC WARRANTY	Si	ALES TAX	7.250%	\$5,293.88
CREDIT LIFE YES XN	O ON THIS VEHI	CLE SEE THE	DISCLAIMER OF	DMV	FEES @ 3300	00	\$0.00
	WARRAN'	TY ON THE BA	CK OF THIS		DOC FEES		\$80.00
ı		CONTRACT.			TIRES		\$10.50
				OL	IT OF STATE I	EE	\$0.00
				TOTA	L PRICE (PER	UNIT)	\$79,343.38
							\$0.00
DEPOSIT CHECK CREDIT	CARD CASH	CHECK NUM	1BER		DEPOSIT		\$0.00
TRADE INFORMATION							
YEAR MAKE MODEL	# OF AXLES	SERIAL NU	JMBER	MILEAGE	l WE	IGHT	
BODY	1				APPRAISAL	DATE	
							\$0.00
TRADE ALLOWANCE AS	TRADE	PAYOFF					
APPRAISED				Gra	nt		\$0.00
\$0.00	50	.00					
				UNPAID	BALANCE	(PER UNIT)	\$79,343.38
Your signature and subsequent accordance of this velocities a potential sale of this velocities with the control of the contro	nicle subject to yo	ur providing	2. I have review	ed this order and	d fully understa	nd that my new	unit will be equipped

PURCHASERS CERTIFICATION

- standard equipment as designated by the manufacturer at time of delivery; and
- 1. I hereby certify that this order includes all of the terms and conditions on both the face and reverse side hereof, that this order cancels and supersedes any prior agreement and as of the date hereof comprises the complete and exclusive statement on the terms of the agreement relating to the subject matters covered hereby, and
- 3. I certify that I am of legal age to execute binding contracts in these state. I have read the printed matter on the front and back hereof, and agree to it as a part of this order the same as if it were printed above my signature.

THIS ORDE	R NO VALID UNLESS SIGNED AND ACCEPTED BY	Signed		Purchaser
THE	DEALER OR AN AUTHORIZED MANAGER	Purchaser's		
		Name	LAKE COUNTY SHERRIF'S OFFICE	
APPROVED		Street	116	
3	Dealer or Authorized Representative	Address	4913 Helbush Drive	Lake
		City, State		County
		and Zip	Lakeport, Ca 95453	
		Business Phone	(707)262-4089	

CONTINUATION OF TERMS AND CONDITION CONSTITUTING A PART OF PURCHASE ORDER

Provisions Applicable On Sale Of New Vehicles

- 1. PRICE REVISION: In the event the price to Dealer of the series and body type order by Purchaser Is changed by the manufacturer prior to delivery to purchase, Dealer has the right to accordingly change the cash delivered price to Purchaser, provided that if Purchaser does not agree with such price change, Purchaser may cancel Purchase Order, in which event if a used vehicle has been traded-in as a part of the consideration for the vehicle purchased by Purchaser upon payment of a reasonable charge for storage and repairs (if any) or, if such traded-in vehicle has been previously sold by Dealer the amount received therefore less a selling commission of 15% and any expense (for storage, insuring, conditioning, or advertising) shall be returned to Purchaser.
- 2. It is understood that there is no relationship of principal and agent between the dealer and manufacturer and that the dealer is not authorized to act, or attempt to act, or represent himself, directly or by implication, as agent of the manufacturer, or in any manner assume or create, or attempt to assume or create, any obligation on behalf of or in the name of the manufacturer.
- 3. There are NO WARRANTIES, express or implied, made by the Selling Dealer or the Manufacturer on the new vehicle or chassis described on the front of this order, except the most recent printed manufacturers warranty or warranties applicable to such new vehicle or chassis which are made a part of this order as of here set forth in full. A copy of such manufacturer's warranty or warranties will be furnished to the purchaser upon delivery or vehicle or chassis, and they shall be expressly, IN LIEU OF any other express or implied warranty, condition or guarantee on the new vehicle, chassis, or any part therefore, including any implied WARRANTY of MERCHANTABILITY or FITNESS and of any other obligation on the part of the manufacturer or the Selling Dealer.
- 4. NO WARRANTIES, express or implied, of MERCHANTABILITY or FITNESS or otherwise, are made by the Selling Dealer or the manufacturer with respect to any used vehicle or chassis described on the front or this order except such warranty, if any, as may be expresses completely in writing by the Selling Dealer or the manufacturer on this order or separate instrument delivered to the purchaser. The applicability of any such warranty shall be subject to all the terms and conditions thereon stated.

Provisions Applicable On Sale Of Either A New Or Used Vehicle

- 1. DISCLAIMER OF WARRANTY ON NEW OR USED VEHICLE: The dealer hereby expressly disclaims all warranties, either expressed or implied, including any implied warranty of merchantability or fitness for a particular purpose, and the dealer neither assumes nor authorizes any other person to assume for it any liability in connection with the sale of the vehicle.
- 1A. NOTIFY SELLER WITHIN 20 DAYS: Purchaser shall give notice to seller of any breach of contract or breach or express of implied warranty applicable to the goods within twenty (20) days of the time he/she discovers or should have discovered the said breach or the purchaser shall be barred from any remedy for the breach. Purchaser shall thereafter return the goods to the seller, or anyone designated by the seller, within twenty (20) days after the notice of breach to allow the seller the opportunity to cure the said breach or the purchaser shall be barred from any remedy for the breach.
- 2. USED TRUCK "AS IS" DISCLOSURE: This Unit is being sold "AS IS". This means that if there is anything wrong with this vehicle after you accept delivery of it you, not Pacific Holding Company, are responsible for any repair.
- Again you are buying this unit "AS IS". No warranty is expressed or implied, nor is Pacific Holding Company or its representatives saying that this unit is suitable for any function or task. We specifically do not warrant, guarantee, or promise that it is free of any defects whether they are known or unknown to us or apparent to you.

By signing this document you are assuring us that you have done the following:

- 1. Inspected the truck and found it to be as we represented it to you. All repairs that we told you we would do have been done.
- 2. No one in the dealership has made any promises to you that have not been met.
- 3. You understand this document and agree to its terms.
- 3. REAPPRAISAL OF THE TRADED-IN VEHICLE: If as vehicle has been traded in as a part of the consideration for the vehicle ordered by purchaser hereunder and such vehicle is not delivered to Dealer until delivery to purchaser of the vehicle purchased by purchaser, such traded-in vehicle shall be reappraised at that time and such reappraisal value shall determine the allowance made for such vehicle. In no event will the vehicle fail to comply with dealer's trade package agreement without reappraisal. If such reappraisal value is lower than the original allowance therefore shown on the face of the Purchase Order. Purchaser may, if dissatisfied therewith, cancel this Purchase Order, provided, however, that such right to cancel is exercised prior to delivery of the vehicle ordered hereunder to the purchaser and surrender of the traded-in vehicle to Dealer.
- 4. PURCHASER'S WARRANTY OR TITLE: Purchaser Warrants that the traded-in vehicle is his/hers property free and clear of all liens and encumbrances except as otherwise noted on the title and he/she will deliver a certificate thereto promptly.
- 5. FAILURE OR REFUSAL TO ACCEPT DELIVERY: Unless this Purchase Order shall have been cancelled by Purchaser under and in accordance with the provision of paragraphs "1" or "1A" above, Dealer shall have the right, upon failure or refusal of purchaser to accept delivery of the vehicle ordered to comply with the terms of this Purchase Order, to retain as liquidated damages any cash deposit made by Purchaser, and, in the event a vehicle has been traded-in as a part of the consideration for the vehicle ordered by Purchaser hereunder to sell such traded-in vehicle and reimburse himself with the proceeds of such sale for the expense specified in paragraph "1" above and for such other expenses and losses as Dealer may incur or suffer as a result of such failure or refusal by Purchaser

thereof covered by the Purchase Order where such failure to deliver or delay is due, in whole or in part, to any cause other than the negligence of Dealer

Signature	Date	



00

NorCal Kenworth - Bay Area B400

Lake County Sheriffs Office

4913 Helbush Drive

1755 Adams Avenue

San Leandro, California United States 94577

Phone:

Fax:

Email:

jim.matthews@norcalkw.com

Phone:

Fax:

Contact Email:

Prepared for:

Gavin Wells

Lakeport, California United States 95453

(707) 262-4228

Vehicle Summary

Unit Chassis

T370 SERIES 12000 Fr Axle Load (lbs): Model: CONVENTIONAL 21000 Rr Axle Load (lbs) TRACTOR Type: 66000 G.C.W. (lbs): T370 MD Description:

Road Conditions: **Application**

Local pickup & delivery. 80 Class A (Highway) Intended Serv.: Vehicles which haul 10 General freight Class B (Hwy/Mtn) Commodity: 10

Class C (Off-Hwy) Class D (Off-Road) **Body** Maximum Grade:

6 Type: 155 0.0 Wheelbase (in): Length (ft): 33 0.0 Overhang (in): Height (ft): Fr Axle to BOC (in): 68 Max Laden Weight (lbs): 87 Cab to Axle (in):

Cab to EOF (in): 120 **Trailer** Overall Comb. Length 228 No. of Trailer Axles:

Dry van Type: Length (ft): 40.0 Special Req. U.S. Domestic Registry, 50-State Height (ft): 13.5 36

Kingpin Inset (in): 0 Corner Radius (in):

Restrictions

120 Length (ft): 102 Width (in): 13.5 Height (ft):

Date: Approved by:

Note: All sales are F.O.B. designated plant of manufacture.



Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

T370 SERIES CONVENTIONAL 4/24/2018 3:15:16 PM Incomplete Model Number: Printed:

Quote/DTPO/CO: Q34840228 Jul 1, 2017 Effective Date: Version Number: 40.30 Jim Matthews Prepared by:



NorCal Kenworth - Bay Area B400

Lake County Sheriffs Office 4913 Helbush Drive

1755 Adams Avenue

San Leandro, California United States 94577

Phone:

Fax: Email:

jim.matthews@norcalkw.com

Lakeport, California United States 95453 Phone: (707) 262-4228

Fax:

Contact Email:

Gavin Wells Prepared for:

		Prepared for: Gavin Wells	
Data	Code	Description	Weight
Model 0000370	0	T370 SERIES CONVENTIONAL	9,642
		Electric Door locks LH/RH; Ignition & doors keyed alike; Single electric horn; Single-piece windshield; Electric windshield wipers, 2-speed plus intermittent; Electric windshield washers; Steering wheel 18in. 4-spoke; Glovebox door with locking latch; Dash-mounted cruise control with switches;Turn signal switch with column-mounted dimmer; Standard dash panels include gray w/ burl wood accents; Slate Gray interior primary color; Dark Slate Gray seat color; Floormat; Inside sunvisor, LH/RH; Door courtesy lights; Under-dash center console with 1 cup holder, 1 ashtray & 1 lighter.	
0070006	0	T370 Class 7: medium-duty Conventional.	0
0072000	0	Chassis operation will not include a stationary application. Stationary operation is defined as running the engine under load while stationary at a substantial fraction of engine gross horsepower (60% or greater) for an extended period of time (longer than 5 - 10 minutes).	0
0080050	0	CARB Idle Emissions Reduction Feature for PX-7 and PX-9	0
0090015	0	Medium-duty 4x2 automatic.	0
0091090	0	General freight	0
0093005	0	Local pickup & delivery. Vehicles which haul freight, typically operating within a 100-mile radius, on public streets & highways, & other paved surfaces, including limited Class C roads. Includes package & freight delivery, as well as fuel oil or petroleum distribution, etc. Road usage: minimum 3% Class B, do not code for Class D.	O
0096080	0	Dry van Include beverage trailer, curtain trailer, and chip trailer	0
0098025	0	U.S. Domestic Registry, 50-State	0
Engine 9 E		and a	
Engine & E 0129546		PACCAR PX-9 350 2017 350@2000 321@2200 1150@1400 Includes turbo exhaust brake, no code is used. Diagnostic Plug for data	555
		link, Oil Cooler, Aluminum Flywheel Housing. N09200 N205 120Standard Maximum Speed Limit [LSL] N09220 N207 0Expiration Distance N09240 P09 120Hard Maximum Speed Limit	
		N09260 P14 69Maximum Accelerator Pedal Vehicle Speed N09280 P16 0Accelerator Lower Droop	
		Handellehad anti-un may require review/prometry	

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: Effective Date: Prepared by:

4/24/2018 3:15:16 PM Jul 1, 2017

Jim Matthews

Incomplete

Model Number: Quote/DTPO/CO: T370 SERIES CONVENTIONAL Q34840228

Version Number:

40.30



Data	Code	Description	Weight
		N09300 P19 69Maximum Cruise Speed N09320 C143 0Cruise Control Lower Droop N09360 N203 252Reserve Speed Function Reset Distance N09380 N202 0Maximum Cycle Distance N09400 N206 10Maximum Active Distance N09420 N201 0Reserve Speed Limit Offset N09440 P11 NOEngine Protection Shutdown N09460 P06 NOGear Down Protection N09480 P26 1400.Max PTO Speed N09500 P02 NOCruise Control Auto Resume N09500 P04 NOAuto Engine Brake in Cruise N09540 N209 0Expiration Distance N09540 N209 0Expiration Distance N09560 P520 YESEnable Idle Shutdown Park Brake Set N09580 P32 5Timer Setting N09600 P233 YESEnable Impending Shutdown Warning N09620 P234 60Timer For Impending Shutdown Warning N09640 P516 35Engine Load Threshold N09680 P33 NOIdle Shutdown Manual Overrule N09720 P230 YESEnable Hot Ambient Automatic Overrule N09740 P46 40Low Ambient Temperature Threshold	
1000155	0	N09780 P47 80High Ambient Temperature Threshold Prospector version 41.2	0
.000.00		Replaces Prospector version 41.1	
1000683	0	Effective VSL Setting 65.0 MPH (USA)	(
1000858	0	Engine Idle Shutdown Timer Disabled	C
1000859	0	Enable EIST Ambient Temp Overrule	C
1000891	0	Eff EIST NA Expiration Miles Use only with MX and Cummins engines	C
1002060	S	Air compressor: Cummins 18.7 CFM For Cummins And PACCAR PX engines.	0
1031130	S	Air Cleaner: Dry-type firewall mounted w/filter restriction indicator.	C
1105230	0	Fan Hub: Horton 2-Speed for ISL9, ISL-G, PX-8 or PX-9	C
1121200	S	Cooling module: 1000 square inches T170/T270/T370/T470. Includes metal surge tank on T170/T270/T370.	C
1247194	0	Exhaust:2017 EPA RH Under Cab DPF/SCR For PX-9 w/ Single Vertical RH Side of Cab Tailpipe.	215
1290148	0	Tailpipe: 5 in. single 48 in. 45 degree curved. For use with any Exhaust other than SCR Independent.	5
1321145	0	Fuel Filter:Fleetguard FS1003 Fuel/Water Separator for PX-9	C
1321200	0	Run Aid:None *For Fuel Filter	C
1321300	0	Start Aid:None *For Fuel Filter	C

Unpublished options may require review/approval.	
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.	

Printed: Effective Date: Prepared by: 4/24/2018 3:15:16 PM Jul 1, 2017

Jim Matthews

Incomplete

Model Number: Quote/DTPO/CO: T370 SERIES CONVENTIONAL Q34840228

Version Number:

40.30



Data	Code	Description	Weigh
1700149	0	Retarder Jacobs for PX-8/9 ISL w/ 3-way switch Replaces the standard turbo brake for PX-8 engines.	57
1816260	S	Alternator: PACCAR 160 amp, brush type	C
1821220	S	Batteries: 2 PACCAR GP31 threaded post (700-730) 1400-1460 CCA dual purpose.	0
1836100	S	Starter: PACCAR 12 volt electrical system. W/ centralized power distribution incorporating plug-in style relays. Circuit protection for serviceability, 12-volt light system w/circuit protection circuits number & color coded.	0
1840006	0	Battery disconnect switches 2, mounted in cab Requires battery box LH under.	0
1900996	0	Jump start terminals under hood.	0
ransmissi	ion & Cli	utch	
2011192	0	Transmission: Allison 3000HS 5-speed w/o PTO drive gear. 5th Gen Controls. Includes heat exchanger & oil level sensor. Highway Service only as defined by Allison. CTransynd transmission fluid is standard on all Allison 1000, 2000, 3000 & 4000 series transmissions.	98
2401405	0	Driveline: 2 Dana standard-duty; 1 centerbearing. *Standard duty is 1710 series.	77
2410018	0	Torque converter included w/Allison Transmission.	0
2410204	0	Delete Allison FuelSense	0
2410244	0	J1939 Park Brake Auto Neutral	0
2429358	0	Rear transmission support springs for transmission PTO applications are required to ensure that engine flywheel housings are not overloaded when transmission PTO's are installed.	0
ront Axle	& Fauin	ment	
2502012		Dana Spicer D-1201IL Front Axle rated 12K 3-1/2in. drop. Use with Air Disc Brakes Only.	-36
2603006	S	Front brakes included w/ front hub package.	0
2701018	0	Bendix 14.6K RSD Air Disc Brake Package includes splined rotor for air disc brakes with aluminum LMS hub pilot hubs, hubcaps. For use w/ 22-1/2in. Wheels.	11
2863003	0	Front Springs: Taperleaf 12K w/ shock absorber 54 in. T270/370 only for use on air disc brakes/RSD 2010+ chassis w/ 22.5in. wheels only.	43
2895223	S	Single power steering gear: 13.2K for air brakes.	0
2900903	0	Front air disc brake dustshield includes pad air disc brakes only.	1

Rear Axle & Equipment

Dimensiona	Unpublished o Il and performance data for unpu	ptions may require r ublished options ma		yed in PROSPECTOR.
Printed:	4/24/2018 3:15:16 PM	Incomplete	Model Number:	T370 SERIES CONVENTIONAL
Effective Date:	Jul 1, 2017	·	Quote/DTPO/CO:	Q34840228
Prepared by:	Jim Matthews		Version Number:	40.30

35576-8AF8-0000 Page 4 of 10



Weigh	Description	Code	Data
18	Single Dana Spicer S21-170 single reduction rear axle. Single rear axle rated at 21K.	0 0	3031170
	Rear Axle Ratio - 4.78.	3 O	3200478
	Single rear brakes included w/rear hub package.) S	3300000
-49	Single 23K Bendix RSD Air Disc Brake package includes rear air disc brakes, splined rotor for air disc brakes with aluminum LMS hub pilot hubs. For use w/ 22-1/2in. wheels.	2 0	3401022
)	Spring brakes included w/ single rear air disc brakes.	4 O	3485004
)	Bendix 4S/4M anti-lock brake system.	6 S	3495226
2	Wheel Differential Lock for Dana Spicer Axles S21-170, S21-190, S23-170, S23-190, S26-190 & S30-190; adds D to the end of the axle part number.	1 0	3531001
-4	Rear suspension: single Hendrickson HAS230 23K. Welded crossmember and gussets w/shocks at 8.8 in. height. Mediumduty for use with air disc brakes only. Engine < 1351 Lb Ft. Includes air suspension dump valve.	9 0	3632279
		/heels	Tires & Wh
	Front Tires: Bridgestone R283A Ecopia 11R22.5 14P	3 O	4070016
6	Rear tires: Bridgestone M726ELA 11R22.5 14PR	4 0	4277444
	Rear Tire Quantity: 4	4 0	4900004
	Front Wheel: Accuride 51408 22.5x8.25 steel Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 2-hand holes. Air disc brake compatible.	5 O	5042275
-2	Rear Wheel: Accuride 51408 22.5x8.25 steel Steel Armor[TM] powder coat, hub-pilot mount. 7400lb. maximum rating. 2-hand holes. Air disc brake compatible. Code is priced per pair of wheels.	5 O	5242375
	Powder coat blacksteel wheel. Use in conjunction with front, dual front, rear, spare or lift axle wheel code(s). All wheels on chassis must have same finish color.	3 0	5853908
	Rear Wheel/Rim Quantity: 4	4 0	5900004
	nt	Eauipmen	Frame & Ed
-3	Frame Rails: 10-5/8 x 3-1/2 x 5/16 in. Steel to 308 in. Truck frame weight is 2.91 lbin. per pair of rails. Section modulus is 14.80 cu.in., RBM is 1,776,000 in-lbs per rail. 120,000 PSI yield. Heat treated. Frame rail availability may be restricted based upon application, axle/suspension capacity, fifth wheel setting, or component/dimensional specifications. The results of the engineering review may result in a change to the requested frame rail. If a change is required Kenworth Application Engineering will advise the dealer of the appropriate material specification for a substitute rail.		6054250
	Bumper: Aerodynamic, Painted. Requires a bumper setting code.) S	6308710
	40.9 in. Bumper setting. Requires a bumper code.	9 S	6319409
1	Removable Front Tow Hooks: 2.	5 0	6321005

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: 4/24/2018 3:15:16 PM Incomplete Model Number: T370 SERIES CONVENTIONAL Guote/DTPO/CO: Q34840228
Prepared by: Jim Matthews Version Number: 40.30



Weight	Description	Code	Data
0	Front mudflaps.	S	6390103
0	Battery box: Steel parallel under w/ aluminum diamond plate cover w/ step w/ aluminum step brackets.	S	6404406
O	Battery box location: LH Side.	0	6409901
C	T270/370 Non-polished 2010 or later DPF/SCR cover with cab access step assembly, RH under. End plates will be painted standard black frame color.	0	6451059
C	One-piece welded crossmember assembly with 12mm frame fasteners, center and rear frame. Standard crossmember.	S	6490122
17	Bolted Rear Cab Support Crossmember. Replaces T3 standard.	0	6490430
577	Fifth Wheel: ILS Air, Hol FW35L018XL00 18.0 in. slide, 10.11 in. height. Inboard mounting angles, 55K vertical rating, LH release. Air slide control valve standard in dash. Accommodates a 2 in. SAE kingpin. Requires some style of trailer connections.	0	6544030
(FW rear/fixed setting behind bogie 2 in indicates rearmost setting measured rearward from centerline of tandem or single rear axle	0	6690020
11	Holland: PH-30RP41 pintle hook mounted on 15,000lb rear suspension crossmember for use w/ Reyco, HAS, & Neway suspensions. For yarding dollies, no trailers. 6,000lb vertical rating.	0	6710158
20	Rear mudflap arms: Fleetline FF30SS, tapered spring loaded & stainless steel.	0	6721144
Ś	Rear mudflap shields: White plastic antisail w/ Kenworth logo.	0	6722000
43	Quarter Fenders: Black Polypropylene w/ painted steel brackets, single post mounted, 21 in. white top flap with logo.	0	6737120
(Square end-of-frame w/o crossmember; non-towing.	S	6742009
(Fuel Tank: 45 US gallon rectangular steel BOC replace.		F uel Tanks 7134045
	Rectangular DEF tank. 7.5 gallons of useable volume. The tank will be located just forward of the under cab component on the side you specified. Standard capacity is calculated by fuel capacity of the vehicle and will accommodate two diesel fill-ups for every DEF fill-up. For 1:1 DEF fuel fill ratio, add 7889204.	0	7722008
3	Standard DEF to fuel fill ratio: 2:1 or greater.	0	7889203
10	DEF tank location is on the LH.	0	7889604
	Location: 45 gal fuel tank RH behind cab	0	7930045

Cab & Equipment

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	4/24/2018 3:15:16 PM	Incomplete	Model Number:	T370 SERIES CONVENTIONAL	
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34840228	
Prepared by:	Jim Matthews		Version Number:	40.30	



Weight	Description	Code	Data
0	Cab: Curved Glass Conventional. Cab Includes aluminum & fiberglass fully hucked cab w/ all aluminum bulkhead doors & continuous stainless steel piano-style door hinges. Single electric horn standard. Incandescent exterior lights include diagnosable bulb detection and warning. Trailer cable on tractors includes integrity detection. Standard features include multiplex wiring for interior lights, automated pre-trip inspection, short and open check diagnostics. Warning alarm will sound when lights are left on.	S	8024310
0	Hood: Sloped aerodynamic hood includes grill & separate bumper.	S	8090310
0	Cab heater: W/integral defrosters & A/C 45,000 btu cab heater. No sleeper heater/AC. Includes 5 mode rotary control. T660 include filter media.	S	8108010
10	Adjustable telescoping tilt steering column.	0	8201200
0	5 sets of keys. Replaces standard 2 sets of keys.	0	8203060
0	Gauge: Dash mounted air filter restriction gauge.	0	8220106
0	Gauge: Oil Temperature Gauge Transmission. The NavPlus HD unit includes a virtual transmission oil temperature gauge.	0	8226667
0	KW Driver Information Center: Includes fuel economy, RPM display, trip information, truck information, diagnostics, gear display, alarm clock.	0	8282004
0	Instrument package: Includes speedometer, tachometer, fuel gauge, engine coolant temperature gauge, engine oil pressure, voltmeter. Class 8 also includes primary & secondary air reservoir gauges & an air application gauge. DEF level gauge and warning lamp are included with 2010+ engines. Engine hour meter and outside air temperature readouts are standard. Primary read out will be MPH. Add 8240620 to switch primary scale to KPH in Canada.	S	8282009
C	Cab interior: Pinnacle. Includes vinyl headliner & cab back panel, slate gray interior, dark slate gray seats, floormats, LH/RH inside sunvisor & door courtesy lights.	S	8330003
2	Driver seat: Kenworth Air cushion Plus HB vinyl. Standard features includes 7 in. fore and aft slide adjustment w/isolator, 6- 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted and includes a map pocket. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0	8410191
33	Rider seat: Kenworth Air cushion Plus IB vinyl. Standard features includes 7 in, fore and aft slide adjustment w/isolator, 6- 23 degree recline, air suspension with cover, dual armrests, and single chamber air lumbar support. Seat cushion is 20 inches wide w/ 2-position tilt and 2-position front cushion extension. Seat material has a horizontal stitch pattern and is 2-tone in color. Seat back is carpeted. Seat is manufactured by National. Includes inside visor and retractable 3-point matching seat belts. Grey seat belts.	0	8480181

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:4/24/2018 3:15:16 PMIncompleteModel Number:T370 SERIES CONVENTIONALEffective Date:Jul 1, 2017Quote/DTPO/CO:Q34840228Prepared by:Jim MatthewsVersion Number:40.30

35576-8AF8-0000 Page 7 of 10



40.30

Data	Code	Description	Weigh
8490150	0	Seat color: Jet Black.	(
8601421	0	Kenworth Radio with AM/FM/WB/USB and Bluetooth	4
8700083	0	Under-dash center console: W/2 cup holders, 1 ashtray, 1 lighter, 1 12V outlet & a storage compartment.	
8700144	0	Dome lamp over driver door.	
8700154	0	Self cancelling turn signal: W/head light dimmer switch.	(
8800200	S	Cab access contoured grabhandles, LH/RH.	(
8800400	0	Grabhandle: LH inside door frame above dash.	(
8800401	0	Grabhandle: RH inside door frame above dash.	
8832115	0	Daylite Door: LH/RH includes RH peeper window	(
8841629	0	Air Horn Mounted On Rear Side of LHUC Battery Box	
8850235	0	Dual convex mirror 8.5 inch w/ offset mounting below regular mirror, and non-heated.	(
8850300	S	Look-Down, Pass. Door, Stainless 8.5x4.4	
8867202	0	Mirror: Dual Moto heated mirrors 7 in. x 16 in. LH & RH remote controlled. Switch located on door pad.	•
8869005	S	Mirror brackets 8-1/2 ft load width.	
8871438	S	Rear Cab Stationary Window 17 in. x 36 in.	
8879213	0	Electric-powered LH & RH door window lifts. Switch located on door.	
8890134	0	Exterior aerodynamic sunvisor w/ integral marker lights.	
i ghts & In 9010801		nts Headlamps: Halogen Projector Low Beam, Halogen Complex Reflector High Beam	
9026205	0	Marker Lights: Five aerodynamic, LED mounted in sunvisor.	
9030010	S	Turn Signal Lights: Mounted on fender	
9052011	0	Dual Flush Floodlights: First Set	
9059911	0	Floodlight Location: Located Mid - First Set	
9070138	S	Combination Stop, Tail, Turn & Backup Lights RH & LH.	
9090000	0	Daytime Running Lamps.	
9090126	0	Electric Backup Alarm: Meets SAE J994 & OSHA requirements.	

Unpublished options may require review/approval. Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.					
Printed:	4/24/2018 3:15:16 PM	Incomplete	Model Number:	T370 SERIES CONVENTIONAL	
Effective Date:	Jul 1, 2017		Quote/DTPO/CO:	Q34840228	

Version Number:

Prepared by:

Page 8 of 10 35576-8AF8-0000

Jim Matthews



Data	Code	Description	Weight
9090151	0	Wiring:Cust. Install Trlr Elec. Brake Controller. Class 8/T4 Content Includes Dash Signals: Ignition Power (20A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To EOF Junction Box. These Signals Are Located Near The NavPlus HD Area. No Need To Code For An Additional End of Frame Junction Box. EOF Junction Box Signals Are: Ground, Tail Lamp, Marker Lamp, Left Turn, Right Turn, Stop Lamp and Electric Trailer Brake Controller Wired To Dash. Medium Duty (not T4) Content Includes A MP 280 Series Connector In Dash Near Driver Door Connections With Signals: Battery Power (40A), Ground, Stop Lamp and Electric Trailer Brake Controller Wired To Chassis Connector. Medium Duty (not T4) 2 Way Deutsch Chassis Connector Located Near Back of Cab, With Signals: Ground and Electric Trailer Brake Controller Wired To Dash Connector.	
9090845	0	Circuit Breakers: Replacing fuses. Does not apply to any 5-amp fuse box position. Brakers include stop/brake/turn, tail lamp, high & low beams, marker/clearance lamps, horn, fuel heat, gauges, air dryer, HVAC controls, panel lamps. Some circuits will remain fuses.	0
Air Equipm 9101215		Air Dryer Bendix AD-IS heated Puraguard	0
9108001	0	Moisture ejection valve w/ pull cable drain.	0
9110037		Air & Electrical Supply Kits: Tractor BOC-mounted kit w/ slidebar, spring hanger and composite gladhand/light plug holder mounted on back of cab/sleeper. Kit includes dash mounted trailer air supply valve, trailer hand control valve, and hoses/fittings for the valves. Dash mounted parking brake valve and tractor protection valve are standard. Air lines are detachable at one end only, light lines are detachable at both ends. Conspicuity components are standard.	19
9121112	0	Coiled air & light lines replacing straight lines . Included in tractor kit. 12ft working length.	0
9140328	0	Trailer ABS electric supply through SAE J560 7-pin connector per TMC RP137).	0
Extended V	Varrant _s	v	
9200008		Base Warranty - PACCAR PX-9 Engine 24 months / 250,000 miles / 402,336 km / 6250 hours.	0
9200113	0	Severe Service Medium-duty Warranty: 1-year/ 50,000 miles.	0
Miscellane	ous O	Ship to Dealer.	0
9409852	0	GHG Secondary Manufacturer: Does Not Apply	0
	0	Warning triangle reflector kit: Floor mounted parallel to back wall between seats. Kit consists of 3 triangles in plastic carrying case. For day cab only.	
9490406	0	One 5 lb. dry chemical type fire extinguisher mounted outboard of rider seat. Class ABC.	11
Die	mensiona	Unpublished options may require review/approval. al and performance data for unpublished options may vary from that displayed in	PROSPECTOR.
Printed:			O SERIES CONVENTIONAL
Effective Date: Prepared by:		Jul 1, 2017 Quote/DTPO/CO: Jim Matthews Version Number:	Q34840228 40.30

35576-8AF8-0000 Page 9 of 10



Data	Code	Description	Weight
Paint			
9700000	0	Paint color number(s). N97020 A - L0006 WHITE N97200 FRAME N0001 BLACK N97700 BUMPER L0006 WHITE	0
9943001	0	Bumper Painted Color A	0
9943050	0	Day Cab Standard Paint	0
9944820	0	1 - Color Paint - Day Cab Color will be White if no other color is specified.	0
9965510	S	Base coat/clear coat. The Kenworth Color Selector contains additional instructions, as well as information on Kenworth paint guidelines and surface finish applications. Kenworth is standard with Dupont Imron Elite paint.	0
Total Weigh	nt		11588 lb

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.

Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed: Effective Date: Prepared by: 4/24/2018 3:15:16 PM Jul 1, 2017

Jim Matthews

Incomplete

Model Number: Quote/DTPO/CO: Version Number: T370 SERIES CONVENTIONAL Q34840228

40.30